Large-Scale Batch Scanning Made Easy

OpScan® 16 Optical Mark Read Scanner

Trust the Scantron family of high-precision, high-capacity data collection tools, with their proven optical mark recognition (OMR) features, to meet your large-scale data management needs. The OpScan 16 OMR scanner provides rugged reliability, confidence in accuracy, and total ease of operation.



Trust the Scantron brand

Scan a Wide Variety of Paper

Multiple sheet detector ensures

forms feed correctly, even if the

paper varies in thickness.

More than 40 years of data capture expertise provides the quality and reliability you deserve.

Control Scanning With a Touch

Control panel ensures easy onetouch start and stop scanning. Sensors indicate where forms are throughout so you can clear extra forms before resuming.

Sort Scanned Forms

Ensure continuous rapid scanning by sending forms with errors to a separate output bin.

Eliminate Errors

Aligns forms automatically for the most accurate results possible.

Take the Guesswork Out of Scanning

Open feed path provides clear view of forms being scanned.

High-Speed Accuracy

Process up to 10,800 sheets/hour, using 16 levels of gray to accurately capture even light marks.



Industrial-strength design and components ensure many years of production scanning and maximum return on investment.

Optional Equipment

- · Print information directly on the sheet being scanned, based on the scanned data, by adding an internal, interactive printer. Print error codes, messages, serial numbers, validation flags, and test scores on each form without slowing down scanning.
- Process data contained in most standard barcode formats using the optional barcode reader.
- Read blue/black pen and pencil marks using the ink read head.
- Develop custom scanning applications and get the most from your investment using ScanTools Plus software for:
 - > Editing, scoring, validating, and displayin data
 - Converting data to commonly used export formata



OpScan 16 Scanner	
Physical Description	 Document Transport: 24" H x 43" W x 24" D (61 cm H x 109 cm W x 61 cm D) Weight: Approximately 194 lbs. (88 kg)
Environment	 Operating Temperature: 60° - 80° F (15.6° C - 26.7° C) Humidity: 40%-60%, noncondensating Heat Dissipation: Maximum 3900 BTUs per hour (total system)
Power	 Standard: 60 Hz ±5%, 115 VAC ±10%, U.S. 3 prong plug. Requires 15 amp dedicated circuit, single phase Optional: 50 Hz ±5%, 100 or 110 VAC ±10%; U.S. 3-prong plug. Requires 15 amp dedicated circuit, single phase 50 Hz ±5%, 220 or 240 VAC ±10%; U.S. 3-prong plug. Requires 7.5 amp dedicated circuit, single phase
Communications	USB 2.0, using a virtual serial port with user-defined protocol.
Operation	 Maximum Speed: 10,800 8½" x 11" (216 mm x 280 mm) sheets per hour Read Head: Pencil (Infrared) Hopper/Stacker Capacities: Input Hopper: 750 sheets; Output Stacker: 750-sheet main and one 200-sheet select stacker Controls: Computer keyboard is primary control, in addition to a convenient Ready button on the control panel Status Indicators: Paper sensor status lights appear on the control panel Forms: 3½" x 7½" to 9" x 12" (85 mm x 191 mm to 229 mm x 305 mm); uses standard Scantron Mark Reflex* or Trans-Optic* forms Connectivity: USB (RS-232 required for optional bar code reader)
Components	 Read Head: 16-level mark discriminating, self-calibrating read head, two-sided reflective read Document Transport: Automatic feed, active sheet deskew, two output stackers Options: Transport printer, Ink read head (blue and black ink), Bar code reader

Product information is subject to change without notice.



GET THE RESULTS YOU NEED TO MAKE INFORMED BUSINESS **DECISIONS TODAY!**

For a free consultation to meet your organization's goals, call 800.722.6876 or visit us at **www.scantron.com** to learn more.

About Us

data you can use. We offer solutions and services, delivered with the quality you expect from decades of experience. Whether you need to work on paper, online, or anywhere in between, Scantron can meet you where you are and help you get to where you want to be.



